



## **duratherm-hto-be-en**



## **DURATHERM HTO**

Engineered for precise and efficient temperature control up to 315°C (600°F) and is a budget solution where heat transfer applications require an environmentally friendly, low cost fluid to meet today's fast paced production demands.

### **APPLICATION**

**Duratherm HTO** is engineered for many years of service and it's ideal for a wide range of closed to atmosphere (inertly sealed) applications including paint, rubber, paper mill calendars, board plants, roofing, textiles, laundry, refineries and asphalt production.

### **THE DIFFERENCE**

**Duratherm HTO's** use of highly refined base stocks ensures excellent thermal stability. Its low volatility also minimizes vapor pressure at elevated temperatures and unlike most other fluids in its class, **Duratherm HTO** contains antioxidants\*, metal deactivators and corrosion inhibitors to further enhance the fluid's longevity and help protect your system.

\*For critical applications where high levels of oxidation are prevalent please consider **Duratherm 600**.

### **ENVIRONMENTAL**

**Duratherm HTO** is environmentally friendly, non-toxic, non-hazardous and non-reportable. **Duratherm HTO** poses no ill effect to worker safety.

### **DISPOSAL**

After its long service life **Duratherm HTO** can easily be disposed of with other waste oils. **Duratherm** supports recycling and encourages oil reclamation programs where possible.

### **SYSTEM CLEANING**

If your existing fluid has let you down and left you with a system full of sludge or carbon, we've developed a full line of heat transfer system cleaners to get your system back to like-new condition. Contact us for complete details.

[www.durathermfluids.be](http://www.durathermfluids.be)



## **duratherm-hto-be-en**

Caption:

Description:

Dimensions: x