



duratherm-hto-be-en



DURATHERM HTO

Engineered for precise and efficient temperature control up to 315°C (600°F) and is a budget solution where heat transfer applications require an environmentally friendly, low cost fluid to meet today's fast paced production demands.

APPLICATION

Duratherm HTO is engineered for many years of service and it's ideal for a wide range of closed to atmosphere (inertly sealed) applications including paint, rubber, paper mill calendars, board plants, roofing, textiles, laundry, refineries and asphalt production.

THE DIFFERENCE

Duratherm HTO's use of highly refined base stocks ensures excellent thermal stability. Its low volatility also minimizes vapor pressure at elevated temperatures and unlike most other fluids in its class, **Duratherm HTO** contains antioxidants*, metal deactivators and corrosion inhibitors to further enhance the fluid's longevity and help protect your system.

*For critical applications where high levels of oxidation are prevalent please consider **Duratherm 600**.

ENVIRONMENTAL

Duratherm HTO is environmentally friendly, non-toxic, non-hazardous and non-reportable. **Duratherm HTO** poses no ill effect to worker safety.

DISPOSAL

After its long service life **Duratherm HTO** can easily be disposed of with other waste oils. **Duratherm** supports recycling and encourages oil reclamation programs where possible.

SYSTEM CLEANING

If your existing fluid has let you down and left you with a system full of sludge or carbon, we've developed a full line of heat transfer system cleaners to get your system back to like-new condition. Contact us for complete details.

www.durathermfluids.be



duratherm-hto-be-en

Caption:

Description:

Dimensions: x