

duratherm-lt-de-en



DURATHERM LT

Engineered for applications requiring process temperatures ranging from -29°C (-30°F) to 315°C (600°F). Ideal for batch processing requiring heating and cooling cycles. Eliminates the need for heat tracing in outdoor applications.

APPLICATION

Durathern LT is an oxidative and thermally stable, high performance, long lasting, environmentally friendly heat transfer fluid. **Durathern LT** is engineered with a broad temperature range offering precise temperature control between -29°C (-30°F) and 315°C (600°F).

Durathern LT is ideal for batch processing requiring heating and cooling cycles and eliminates the need for heat tracing in outdoor applications.

THE DIFFERENCE

Our exclusive additive package, including a proprietary dual stage anti-oxidant, ensures long trouble-free operation. **Duratherm LT** also incorporates metal deactivators, a seal and gasket extender, defoaming and particle suspension agents.

LASTS LONGER

In the heat transfer fluid industry cost is always a concern, however fluid longevity and resistance to harmful fouling are of equal importance.

Air contact is normally detrimental to a fluid. Oxidation can cripple your system and if left unchecked will ultimately cause catastrophic failure. Unscheduled downtime due to oil failure has a high cost and negative effect on production.

The **Duratherm** product line was developed with this in mind. Most other fluids fall short in their protection from oxidation and can quickly foul a system. **Duratherm LT** is engineered to give unsurpassed levels of protection and service life.

ENVIRONMENTAL

Duratherm LT is environmentally friendly, non-toxic, non-hazardous and non-reportable. It poses no ill effect to worker safety and does not require special handling. After its long service life, Duratherm LT can easily be disposed of with other waste oils.

SYSTEM CLEANING

If your existing fluid has let you down and left you with a system full of sludge or carbon, we've developed a full line of heat transfer system cleaners to get your system back to like-new condition. Contact us for complete details.

www.durathermöle.de

1 of 4



duratherm-lt-de-en

Caption:	
Description:	
Dimensions: x	