



## **duratherm-xlt-120-fr-en**



# **DURATHERM XLT-120**

Engineered for long-term operation in heat transfer applications requiring precise temperature control ranging from  $-84^{\circ}\text{C}$  ( $-120^{\circ}\text{F}$ ) up to  $65^{\circ}\text{C}$  ( $150^{\circ}\text{F}$ ).

Ideal for cryogenic applications Duratherm XLT-120's economical cost and wide operating temperature also makes it well-suited for heating and cooling applications found in the food processing, pharmaceutical and chemical industries.

#### **TROUBLE-FREE OPERATION**

Duratherm XLT-120 heat transfer fluid does not require monitoring of concentration or additive levels.

#### **LASTS LONGER**

Duratherm XLT-120 utilizes our exclusive additive system for long-term, trouble-free operation at any temperature, high or low.

#### **ENVIRONMENTAL**

Duratherm XLT-120 is plant and user friendly. Low odors, high flash point and no SARA reportable substances makes Duratherm XLT-120 the wise choice for worker health and safety.

#### **DISPOSAL**

After its extensive service life, Duratherm XLT-120 can typically be disposed of through local waste oil recycling programs. Check your local regulations.

[www.fluidesduratherm.fr](http://www.fluidesduratherm.fr)



## **duratherm-xlt-120-fr-en**

Caption:

Description:

Dimensions: x